

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 06-146001

(43)Date of publication of application : 27.05.1994

---

(51)Int.Cl. C23C 22/00

B32B 15/08

C09D175/00

C23C 22/28

---

(21)Application number : 04-300107

(71)Applicant : ASAHI KAGAKU KOGYO KK  
SUMITOMO METAL IND LTD

(22)Date of filing : 10.11.1992

(72)Inventor : MARU SHUNICHI  
KIYA TOSHIO  
HOB0 YOSHIHIKO  
FUKUTOME HIROSHI  
UEDA NAOTAKA

---

### (54) ORGANIC SURFACE TREATING AGENT FOR ALUMINUM-ZINC ALLOY PLATED STEEL SHEET AND ALUMINUM-ZINC ALLOY PLATED STEEL SHEET TREATED BY THIS AGENT

(57)Abstract:

PURPOSE: To provide the Al-Zn alloy plated steel sheet having excellent alkaline resistance, black rust resistance and lubricity by applying the org. surface treating agent contg. a water-dispersible or water-soluble polyester resin or polyurethane resin to this steel sheet.

CONSTITUTION: The org. surface treating agent for the Al-Zn alloy plated steel sheet is obtd. by incorporating a mixture composed of  $\geq 1$  kinds of the water-dispersible or water-soluble polyester resin or polyurethane resin into this agent. This org. surface treating agent is applied to the surfaces of the Al-Zn alloy plated steel sheet subjected or not subjected to a chromate treatment at 0.3 to 4g/m<sup>2</sup> thickness by dry weight. The chromate treatment is preferably executed at <60mg/m<sup>2</sup> thickness in terms of chromic acid. A resin compsn. compounded with a chromium compd. of  $\geq 30\%$  hexavalent chromium at 0.1 to 5% in terms of chromium oxide is preferably used in the case the steel sheet is not subjected to the chromate treatment.